



Diamond™ Hybrid EM/RFID Premium Hybrid security detection system


The Diamond™ Hybrid Premium system reduces unauthorized removal of library items by detecting the EM & RFID tags in any orientation.



Diamond™ Hybrid EM/RFID Premium Hybrid security detection system

With its modern transparent looks – high density plexiglass in combination with a solid stainless steel construction - the Diamond™ Hybrid Premium system gives an extremely luxurious appearance to any library environment.

The Diamond™ Hybrid Premium system reduces unauthorized removal of library items by detecting EM & RFID tags in any orientation.



0 0

Specifications

Detection:

Depending on the size and type of tag:

- Single aisle width System 2: up to 0.90 meter
- Dual aisle width System 3 : up to 1.80 meter

Features

- Fully digital configuration (DSP)
- · Visual and audio alarm
- Advanced electromagnetic EM technology
- Advanced radio frequent identification (RFID) technology
- Remote maintenance
- Magnetic media safe
- Multiple gate solutions are possible

EM / RFID specification:

- Operating frequency: 366 Hz. / 13,56 MHz.
- Supported tags: all Dialoc ID EM tags and various EM tag suppliers
- ISO 15693 RFID tags, NXP SLI and NXP SLI-X

Option:

• People counter with display

Interface:

Ethernet (TCP/IP), USB, RS232, CAN

Dimensions:

Antenna: $655 \times 100 \times 1900 \text{ mm}$ (w x d x h) Base : $705 \times 120 \times 20 \text{ mm}$ (w x d x h)

Material:

Panel: High density clear PMMA 20mm plexiglass, weather

and UV resistant, 92% light transmission

Base: Stainless steel **Weight:** 36 kg.