



Sapphire[™] EM Self service

Circulation system


Today self-service in libraries is a powerful and crucial service to patrons. The Sapphire $^{\text{\tiny{TM}}}$ is an ergonomically designed hi-tech self service unit that fits perfectly into the logistic process.

It's modular construction gives all the flexibility to libraries who want to migrate to different identification technology today and in the future.

The Sapphire™ EM Self service seamlessly combines barcoding technology for the identification of items and

patron cards with EM technology for optimal security of items by (de) activating the EM tags after successful registration of items. This simple, one-move handling improves efficiency, accuracy and security in a user friendly environment.

The 22" HD touch screen together with the integrated receipt printer, EM (de)activator, barcode scanners for items and cards are designed in one compact stylish high-quality housing, and therefore easy to relocate in a library.



Sapphire[™] EM Self service Circulation system

The Sapphire[™] self service unit comes standard with full circulation software including check-in, check-out and renew functions, preconfigured to connect to an LMS (Library Management Software) through SIP2 which is completely supported.

Options

The Sapphire[™] self service unit is delivered in beige/grey color. Upon request other colors are available.

Specifications

Dimensions

Height: 663 mm Width: 638 mm Depth: 568 mm

Material: stainless steel, PS, high-impact composite

Weight: 37 kg

Functions: Self service: Check -in, check-out

Compatibility: SIP2

Standard: ISO 15.693 / 18.000-3.1 / ISO 28560 / ISO 14443

Certifications: CE / EMC

Check-in / check-out materials: Books / Magazines / Media

Touch PC:

High quality 16: 9 Full HD 22 LCD screen with a wide view angle VA panel. Dust and water proof. (IP65), Chip-set: Intel® QM77, CPU: Intel® 2nd and 3rd generation Intel Core™ i3, i5, i7, mobile processor TPD > 35W

Printer:

Thermal line printing with a 200 dpi print head, print speed of 250mm/second, assuring crisp, clear receipts and eye-catching logos.

Item Identification: 2D barcode imager Patron identification: 2D barcode imager

Item protection: EM technology. (EM (de) activator)

Software option: Dialoc library software* pre-installed and pre-configured. It supports LMS/1LS protocols SIP2 and is data model independent. Access to the

library network via Ethernet is required.

Upon request the Sapphire™ self service unit can be delivered wihout software.

Power: 230 V

Environmental facts: Temperature: + 10°C <> + 45°C



Color options:

