



BOOK TAG DISPENSER

The best way to convert your valuable library materials


The Dialoc ID book tag dispenser is designed for converting, programming and dispensing library labels for books and magazines.

Seamless integration of technologies

The Dialoc ID book tag dispenser is a fast and efficient tool to write data into book tags and setting the EAS and/or AFI bit. The data can be read by using a barcode scanning during

the conversion process. The dispenser is used stand alone as a USB device, must be connected to a pc or laptop, and operates with the YourLib® ID Converter software.

After programming, the tag can be taken from the release paper of the roll. Thereafter a new tag will automatically be offered for programming. The motor driven dispenser can dispense a wide array of labels, as the photocell will detect the beginning of each new label.



BOOK TAG DISPENSER

Specifications

Features:

- Easy to install
- Standard USB connection
- Set/Reset EAS and/or AFI bit
- Designed to work in any environment
- Integrated RFID reader

Functions:

- Conversion from barcode to RFID tag

Compatible protocols:

- ISO 15693 / ISO 18000-3 mode 1

Supported tags:

- iCode Ilt, iCode Sli-(X)(2), 50x50mm and 50x80mm tags

Supported datamodels:

- 3M (numeric and alphanumeric)
- Danish
- Dutch
- ISO 28560 fix
- ISO 28560 object

Software:

- YourLib® ID Converter, optional with YourLib® Advanced Repair license

Technical Specification:

- Operating Frequency: 13.56 MHz.
- Communication interface: USB
- Power Supply: AC230V/50Hz.
- Max. roll diameter: 20cm
- Dimensions: 442 x 320 x 295mm
- Weight: 9kg
- Average speed: 375 tags per hour

Applications:

- Libraries, Archives

